

# OpenADR 2.0b

# Protocol Implementation Conformance Statement (PICS)

#### Version 1.0.6 Valid for Certification as of September 10, 2013

Manufacturer:	Gridwiz Inc.
Product Type:	VEN
Product Name:	Gridwiz OpenADR 2.0b VEN Standard SDK
Firmware Revision:	V2.0
Tested OpenADR 2.0b Profile Spec version:	1.0.6

#### Disclaimer:

The information provided in this document can be made available to the general public in order to identify the tested versions, features and options.

By signing this document, the manufacturer confirms that all information provided in this document is correct and the applicable features have been tested.

Manufacturer Name: Aridwit Inc.		-
Representative Name and Title: Teddy Hynnwoong	Kim	1 Director
Signature:	-	
Date: 30 - March - 2015		



# **Revisions:**

Version		Changes	Date/Editor
1.0.0	•	Released Version	06/28/13
1.0.1	•	Added additional optional test case conditions	07/28/13
1.0.2	•	Added test case A_E1_0285 and A_E0_0285 to optional list	08/15/13
1.0.4	•	Added test case A_E3_0680 to optional list	08/20/13
1.0.5	•	Added the following test cases to optional list.  A_E2_0435, A_E3_0435, A_E2_0685, A_E3_0685, R1_3070_TH_VTN_1,  R0_8070_TH_VTN_1, R1_3080_TH_VTN_1, R0_8080_TH_VTN_1,  R1_3090_TH_VTN_1,R0_8090_TH_VTN_1, R1_3100_TH_VTN_1,  R0_8100_TH_VTN_1, R1_3120_TH_VTN_1, R0_8120_TH_VTN,  R1_3050_TH_VEN, R0_8050_TH_VEN_1, R1_3060_TH_VEN,  R0_8060_TH_VEN, R1_3120_TH_VTN_1 and R0_8120_TH_VTN.	09/09/13
1.0.6	:	Corrected typo. Removed test case A_E0_0295.	2/11/2014 EP, BD
	•	Mentioned G0_9005.	



# **Table of Contents**

Revisions:	•
Introduction	1
References	1
Abbreviations and Conventions	ļ
Instructions for Completing the PICS	
Documents required for final certification	
Implementation and Supplier Information	
Global Statement of Conformance	
Roles	
Profile Support	
Transports /Exchange Pattern Support	7
Service Support	
Security Support	
Payload Schema Conformance	
Operational Sequence Support10	
Standard Event Signal Support1	
Standard Report Support1	
Alliance "B" Profile Detailed Requirements	)
Implementation Capabilities and Configuration19	֡
Optional Test Case Guidelines	֡



#### Introduction

The purpose of this PICS document is to provide a mechanism whereby a supplier of an implementation based on the following requirements may provide information about the implementation in a standardized manner.

These requirements are drawn from the OASIS Energy Interoperation standard and related schemas. With the exception of OpenADR Alliance schema extensions, payloads generated by OpenADR 2.0b implementations should validate against the Energy Interop schemas.

Information provided by the supplier will be used to assess the implementation's compliance to the requirements, as well as to configure the certification tests performed on the implementation.

#### References

- OpenADR 2.0b Profile Specification 1.0
- OpenADR 2.0b Test Spec V1.0.6
- OpenADR 2.0b Schema

#### Abbreviations and Conventions

The PICS information comprises information in a tabular format as follows:

- Item Column A number which identifies the item in the table
- Capability Column A brief description of the requirement
- Reference Column or Section Header A reference to a specific requirement in the specification
- Status Column Contains notations regarding the requirements
  - o M Mandatory
  - o O Optional
  - o N/A Not applicable
  - o X Prohibited
  - O-i Qualified Optional (mutually exclusive or selectable options from a set identified with the same "I" value)
  - C-i –Conditional (status dependent on support of other optional requirements, identified in footnotes at bottom of table with "i" being a reference integer for the footnote(s))
- Support Column Yes or No answer is required. If feature is not applicable, answer No.
- Values Allowed Column Optional column representing set of values allowed.
- Values Supported Column Optional column where supplier can indicate a set of values supported by the implementation.

Note that all requirement references in the tables on the following pages are with respect to the OpenADR 2.0b Profile Specification, Version 1.0.



#### **Instructions for Completing the PICS**

The first part of the PICS document, System Identification, is to be completed as indicated with the information necessary to fully identify both the supplier and the implementation.

The main part of the PICS document is a fixed format questionnaire. Answers to questionnaire items are to be provided in the rightmost column by simply marking an answer to indicate a choice, typically Yes or No.

If an implementation fails to support a mandatory item, or supports a prohibited item, the supplier should provide supplementary information with the PICS document explaining the rationale for the exception.

Note: The burden of interoperability falls to the VTN implementation. Therefore any certified VTN must support the 2.0A profile and the 2.0B profile including the applicable schemas.

#### **Documents required for final certification**

- This PICS document
- Manufacturers Declaration of Conformity
- Completed Test Report from appointed test house
- Product marketing description for website (50 words)
- Product picture or logo if applicable
- Web link to product

If you would like to postpone posting your product on the OpenADR Alliance website for a period of time (maximum 3 months), please fill out the following section.

(Manufacturer) herewith requests that the su	bmitted product shall not be
posted on the OpenADR Alliance product web page untilsubmittal).	
Name:	
Signature:	



# Implementation and Supplier Information

Date of Statement	30 March 2015
Product Name	Gridwiz OpenADR 2.0b VEN Standard SDK
Product Model Number	GWOADR_20B_VEN_SDK_STD_PULL_HTTP
Version Number(s)	2.0
Non-Default Hardware Configuration	N/A
Non-Default Software Configuration	N/A
Supplier Name, Address, Phone, Email	Gridwiz Inc. 4F, 1010Bldg, 25, Sanun-ro 208 beon-gil, Bundang-gu, Seongnam-si, Gyeonggi, 464-440, Korea
Contact name, email, phone for questions	Seok Lim limseok@gridwiz.com +82-31-698-3487



#### **Global Statement of Conformance**

Requirement	Support	
Are all mandatory capabilities supported for the indicated roles supported by	[x]Yes	[]No
this implementation?		

#### Roles

Item	Role	Status	Support
1	VEN - Full Function	0-1	[x]Yes [ ]No
3	VEN - Energy Reporting Only	0-1	[]Yes [x]No
3	VTN	0-1	[]Yes [x]No

<sup>0-1)</sup> Must answer Yes to one Role. Note that if an implementation supports both VEN and VTN functionality, two separate PICS documents should be submitted, one for each role.

#### **Profile Support**

Requirements Reference: Conformance rule 506

Item	Role	Profile	Status	Support
1	VEN/VTN	"A" Profile	C -1	[]Yes [x]No
2	VEN/VTN	"B" Profile	М	[x]Yes []No

C-1) VTNs must support the A

### **Transports / Exchange Pattern Support**

Requirements Reference: Figure 1, OpenADR 2.0 Certification Levels and conformance rule 37

Item	Role	Transport	Status	Support
1	VEN/VTN	SimpleHTTP - Pull	C-1	[x]Yes []No
2	VEN/VTN	SimpleHTTP - Push	C-1	[]Yes [x]No
3	VEN/VTN	XMPP - Push	C-1	[]Yes [x]No

C-1) VTNs must support all transports and exchange patterns.

\_

C-1) VENs may support ONLY the B profile

C-1) VENs must support at least one item from the list. If SimpleHTTP items are selected this must include the "SimpleHTTP-Pull" option from the list.



#### Service Support

Requirements Reference: Section 7.2.2 and conformance rules 501 and 507

Item	Role	Service	Status	Support
1	VEN/VTN	EiEvent	C-1	[x]Yes [ ]No
2	VEN/VTN	EiOpt	C-1	[x]Yes [ ]No
3	VEN/VTN	EiReport	М	[x]Yes [ ]No
4	VEN/VTN	RiRegisterParty	M	[x]Yes [ ]No
5	VEN/VTN	OadrPoll	C-2	[x]Yes [ ]No

C-1) VTNs and Full Function VENs must support Services. Not supported by Report Only VENs.

#### **Security Support**

Requirements Reference: Conformance rules 67, 68, and 514

Item	Role	Security	Status	Sup	port
1	VEN	SHA1 Security	C-1	[]Yes	[x]No
		-TLS 1.0, 1.1			
		-Client and server x.509 certs with SHA1			
		-Alliance RSA or ECC SHA1 Ciphers			
		-SASL_EXTERNAL (XMPP Only)			
2	VTN	SHA1 Security	C-1	[]Yes	[x]No
		-TLS 1.0, 1.1			
		-Client and server x.509 certs with SHA1			
		-Alliance RSA and ECC SHA1 Ciphers			
		-SASL_EXTERNAL (XMPP Only)			
3	VEN	SHA2 Security	C-2	[x]Yes	[]No
		-TLS 1.2			
		-Client and server x.509 certs with SHA2			
		-Alliance RSA or ECC SHA2 Ciphers			
		-SASL_EXTERNAL (XMPP Only)			
4	VTN	SHA2 Security	C-2	[]Yes	[x]No
		-TLS 1.2			
		-Client and server x.509 certs with SHA2			
		-Alliance RSA and ECC SHA2 Ciphers			
		-SASL_EXTERNAL (XMPP Only)			
5	VEN/VTN	XML Signatures	0	[]Yes	[x]No

C-1) Support for these options is prohibited past an Alliance-defined grace period.

C-2) VTNs must support; VENs must support if simpleHTTP transport is supported.

C-2) Support for these options is mandatory past an Alliance-defined grace period. Select option appropriate to role, mark other as N/A.



## **Payload Schema Conformance**

For each payload generated by a VEN or VTN, indicate if it conforms to the OpenADR B Profile schema. Note that the Status is relative to the Role listed.

Item	Role	Payload	Status for Role	Validates Against B Schema
1	VEN-Pull	oadrPoll	C-1	[x]Yes []No
2	VEN	oadrRequestEvent	C-2	[x]Yes []No
3	VEN	oadrCreatedEvent	C-2	[x]Yes []No
4	VEN	oadrCreateOpt	C-2	[x]Yes []No
5	VEN	oadrCancelOpt	C-2	[x]Yes []No
6	VTN	oadrCanceledOpt	C-2	[x]Yes []No
7	VEN	oadrQueryRegistration	M	[x]Yes []No
8	VEN	oadrCreatePartyRegistration	M	[x]Yes []No
9	VEN/VTN	oadrResponse	M	[x]Yes []No
10	VEN/VTN	oadrCancelPartyRegistration	M	[x]Yes []No
11	VEN/VTN	oadrCanceledPartyRegistration	M	[x]Yes [ ]No
12	VEN/VTN	oadrRegisterReport	М	[x]Yes []No
13	VEN/VTN	oadrRegisteredReport	M	[x]Yes [ ]No
14	VEN/VTN	oadrCreateReport	M	[x]Yes [ ]No
15	VEN/VTN	oadrCreatedReport	M	[x]Yes []No
16	VEN/VTN	oadrUpdateReport	M	[x]Yes []No
17	VEN/VTN	oadrUpdatedReport	M	[x]Yes []No
18	VEN/VTN	oadrCancelReport	M	[x]Yes []No
19	VEN/VTN	oadrCanceledReport	M	[x]Yes []No
20	VTN	oadrCreatedOpt	C-2	[]Yes [x]No
21	VTN	oadrDistributeEvent	C-2	[]Yes [x]No
22	VTN	oadrCreatedPartyRegistration	M	[]Yes [x]No
23	VTN	oadrRequestReregistration	М	[]Yes [x]No

C-1) VENs with SimpleHTTP push support must support oadrPoll, other implementations must not.

C-2) All implementations must support these options except for Report Only VENs.



#### **Operational Sequence Support**

The table below demonstrates the operational sequences and the conditional behavior for each of the services. The VEN oadrPoll interaction pattern and push HTTP acknowledgement (empty payload) of oadrDistributeEvent are not shown in the table. Indicate if all of the behavior shown in each section is supported by the implementation. Brackets are used to indicate conditional behavior which must be supported. Requirements reference: All figures in the B profile specification with interaction diagrams

Item	Service	App Level Exchange Sequence	Status	Supp	ort
1	EiEvent	{VEN: RequestEvent {Reply Limit}}	C-1	[x]Yes	[]No
		VTN: oadrDistributeEvent {Response Required, baseline}			
		{VEN: oadrCreatedEvent {Opt State}			
		VTN: oadrResponse }			
2	EiOpt	VEN: oadrCreateOpt {Availability schedule}	C-1	[x]Yes	[]No
		VTN: oadrCreatedOpt			
		VEN: oadrCancelOpt			
		VTN: oadrCanceledOpt			
		VEN: oadrCreateOpt - {Event Opt State}			
		VTN: oadrCreatedOpt			
3	EiRegisterParty	VEN: oadrQueryRegistration	M	[x]Yes	[]No
		VTN: oadrCreatedPartyRegistration			
		VEN: oadrCreatePartyRegistration			
		VTN: oadrCreatedPartyRegistration			
		VEN/VTN: oadrCancelPartyRegistration			
		VTN/VEN: oadrCanceledPartyRegistration			
		VTN: oadrRequestReregistration			
		VEN: oadrResponse			
		VEN: oadrCreatePartyRegistration			
		VTN: oadrCreatedPartyRegistration			
4	EiReport	VEN/VTN: oadrRegisterReport	C-3	[x]Yes	[]No
		VTN/VEN: oadrRegisteredReport (Create Report *)			
		VEN/VTN: oadrCreateReport (Once or Periodic)			
		VTN/VEN: oadrCreatedReport			
		VEN/VTN: oadrUpdateReport			
		VTN/VEN: oadrUpdatedReport {Cancel Report *}			
		VEN/VTN: oadrCancelReport			
		VTN/VEN: oadrCanceledReport {Report to Follow}			
5	OadrPoll	VEN: oadrPoll	C-2	[x]Yes	[]No
		VTN: Any payload sent by VTN			

C-1) All implementations must support these options, except for Report Only VENs.

C-2) Required for SimpleHTTP Pull VENs only.

C-3)VENs and VTNs are not required to demonstrate initiating piggyback report requests and report cancellations (\*), but must understand them and act upon them if received from the other party. All other payload interactions shown are mandatory.



#### **Standard Event Signal Support**

Indicate which of the following Alliance-defined standard signals are supported by the VEN or VTN . Requirements Reference: Conformance rule 510

Item	Role	Signal Name	SignalType	Status	Sup	oort
1	VEN/VTN	SIMPLE		М	[x]Yes	[]No
2	VEN/VTN	ELECTRICITY_PRICE	Price	М	[x]Yes	[]No
3	VEN/VTN	LOAD_DISPATCH	setpoint	М	[x]Yes	[]No

<sup>1)</sup> The Alliance was still determining VTN report support at the time this was drafted.

#### **Standard Report Support**

Indicate which of the following Alliance-defined standard reports are offered as part of report registration by the VEN or VTN. Requirements Reference: Conformance rule 510

Item	Role	Report Name	Status	Support
1	VEN	METADATA	М	[x]Yes []No
2	VEN	TELEMETRY_UASGE	M	[x]Yes []No
3	VEN	TELEMETRY_STATUS	М	[x]Yes []No
4	VEN	HISTORY_USAGE	C-1	[]Yes [x]No
5	VTN	METADATA	М	[]Yes [x]No

C-1) Optional for full function VENs; mandatory for Report Only VENs.



#### Alliance "B" Profile Detailed Requirements

In addition to the requirements defined by the schema, the OpenADR 2.0b Profile has a detailed set of conformance rules that define the expected behavior of VTN and VEN implementations. As these rules already reflect the testable requirements, there is no need to relist them here. Please refer to the OpenADR 2.0b Profile Specification while indicating which of the following conformance rules are supported by the implementation.

Item (Rule)	Role	Status	Support
1	VTN	C-1	[]Yes [x]No
2	VTN	C-1	[]Yes [x]No
3	VTN	C-1	[]Yes [x]No
4	VTN	C-1	[]Yes [x]No
5	VTN	C-1	[]Yes [x]No
6	VEN	C-1	[x]Yes []No
8	VTN	C-1	[]Yes [x]No
9	VTN	C-1	[]Yes [x]No
10	VTN	C-1	[]Yes [x]No
12	VEN	C-1	[x]Yes []No
13	VTN	C-1	[]Yes [x]No
14	VTN	C-1	[]Yes [x]No
15	VTN	C-1	[]Yes [x]No
16	VTN	C-1	[]Yes [x]No
17	VTN	C-1	[]Yes [x]No
18	VEN/VTN	C-1	[x]Yes []No
19	VEN	C-1	[x]Yes []No
20	VTN	C-1	[]Yes [x]No
21	VEN/VTN	C-1	[x]Yes []No
22	VEN	C-1	[x]Yes []No
23	VEN/VTN	C-1	[x]Yes []No
25	VTN	C-1	[]Yes [x]No
27	VTN	C-1	[]Yes [x]No
29	VTN	C-1	[]Yes [x]No
30	VEN	C-1	[x]Yes []No
31	VEN	C-1	[x]Yes []No
32	VEN/VTN	C-1	[x]Yes []No
33	VEN/VTN	C-1	[x]Yes []No
35	VEN	C-1	[x]Yes []No
36	VEN	C-1	[x]Yes []No
37	VEN	C-1	[x]Yes []No
38	VTN	C-1	[]Yes [x]No
40	VTN	C-1	[]Yes [x]No
41	VTN	C-1	[]Yes [x]No
42	VEN/VTN	C-1	[x]Yes []No
43	VEN	C-1	[x]Yes []No
45	VEN/VTN	C-1	[x]Yes []No
46	VEN/VTN	C-1	[x]Yes []No
47	VEN/VTN	C-1	[x]Yes []No
48	VEN/VTN	C-1	[x]Yes []No
50	VTN	C-1	[]Yes [x]No
51	VEN/VTN	C-1	[x]Yes []No
52	VTN	C-1	[]Yes [x]No



Item (Rule)	Role	Status	Support
53	VEN/VTN	C-1	[x]Yes []No
56	VEN	C-1	[x]Yes []No
57	VEN/VTN	C-1	[x]Yes []No
58	VEN	C-1	[x]Yes []No
59	VEN	C-1	[x]Yes []No
60	VEN	C-1	[x]Yes []No
61	VEN	C-1	[x]Yes []No
62	VEN	C-1	[x]Yes []No
63	VTN	C-1	[]Yes [x]No
65	VEN	C-1	[x]Yes []No
66	VEN/VTN	C-1	[x]Yes []No
67	VEN/VTN	C-1	[x]Yes []No
68	VEN/VTN	C-1	[x]Yes []No
100	VTN	C-1	[]Yes [x]No
101	VTN	C-1	[]Yes [x]No
102	VTN	C-1	[]Yes [x]No
102	VTN	C-1	[]Yes [x]No
104	VTN	C-1	[]Yes [x]No
105	VTN	C-1	[]Yes [x]No
106	VTN	C-1	[]Yes [x]No
107	VTN	C-1	[]Yes [x]No
108	VTN	C-1	[]Yes [x]No
109	VEN	C-1	[x]Yes []No
110	VTN	C-1	[]Yes [x]No
111	VEN/VTN	C-1	[x]Yes []No
112	VEN	C-1	[x]Yes []No
113	VTN	C-1	[]Yes [x]No
114	VEN	C-1	[x]Yes []No
115	VTN	C-1	
116	VEN/VTN	C-1	[ ]Yes [x]No [x]Yes [ ]No
200		C-1	
201	VEN/VTN VEN/VTN	C-1	[x]Yes []No
202	VEN	C-1	[x]Yes []No
1774 TO 1875	VTN	C-1	[x]Yes []No
203	VEN	C-1	[]Yes [x]No
			[x]Yes []No
205	VENIVITN	C-1	[]Yes [x]No
206	VEN/VTN	C-1	[x]Yes []No
207	VEN/VTN	C-1 C-1	[x]Yes []No
	VEN/VTN		[x]Yes []No
209	VEN/VTN	C-1	[x]Yes []No
210	VEN/VTN	C-1	[x]Yes []No
211	VEN/VTN	C-1	[x]Yes []No
300	VEN/VTN	M	[x]Yes []No
301	VEN/VTN	M	[x]Yes []No
302	VEN/VTN	M	[x]Yes []No
303	VEN/VTN	M	[x]Yes []No
304	VEN/VTN	M	[x]Yes []No
305	VEN/VTN	M	[x]Yes []No
306	VEN/VTN	M	[x]Yes []No
307	VEN/VTN	M	[x]Yes []No
308	VEN/VTN	М	[x]Yes []No
309	VEN/VTN	M	[x]Yes [ ]No



Item (Rule)	Role	Status	Support
311	VEN/VTN	М	[x]Yes []No
312	VEN/VTN	М	[x]Yes []No
313	VEN/VTN	М	[x]Yes []No
314	VEN/VTN	М	[x]Yes []No
315	VEN/VTN	М	[x]Yes []No
316	VEN/VTN	М	[x]Yes []No
317	VEN/VTN	М	[x]Yes []No
318	VEN/VTN	М	[x]Yes []No
319	VEN/VTN	М	[x]Yes []No
321	VEN/VTN	М	[x]Yes []No
322	VEN/VTN	М	[x]Yes []No
324	VEN/VTN	М	[x]Yes []No
325	VEN/VTN	М	[x]Yes []No
327	VEN/VTN	M	[x]Yes []No
328	VEN/VTN	M	[x]Yes []No
329	VEN/VTN	M	[x]Yes []No
330	VEN/VTN	M	[x]Yes []No
331	VEN/VTN	M	[x]Yes []No
333	VEN/VTN	M	[x]Yes []No
334	VEN/VTN	M	[x]Yes []No
335	VEN/VTN	M	[x]Yes []No
336	VEN/VTN	M	[x]Yes []No
337	VEN/VTN	M	[x]Yes []No
338	VEN/VTN	M	[x]Yes []No
339	VEN/VTN	M	[x]Yes []No
340	VEN/VTN	M	[x]Yes []No
341	VEN/VTN	M	[x]Yes []No
342	VEN/VTN	M	[x]Yes []No
343	VEN/VTN	M	[x]Yes []No
400	VEN/VTN	M	[x]Yes []No
401	VEN/VTN	M	[x]Yes []No
402	VEN/VTN	M	[x]Yes []No
403	VEN/VTN	M	[x]Yes []No
404	VEN/VTN	M	[x]Yes []No
405	VEN/VTN	M	[x]Yes []No
406	VEN/VTN	M	[x]Yes []No
407	VEN/VTN	M	[x]Yes []No
500	VEN/VTN	C-2	[x]Yes []No
501	VEN/VTN	C-2	[x]Yes []No
502	VEN/VTN	C-2	[x]Yes []No
506	VEN/VTN	M	[x]Yes []No
507	VEN/VTN	M	[x]Yes []No
508	VEN	M	[x]Yes []No
509	VEN/VTN	M	[x]Yes []No
	VEN/VTN	M	[x]Yes []No
510		M	
511 512	VEN/VTN		[x]Yes []No
	VEN/VTN	М О	[x]Yes []No
514	VEN/VTN	U	[ ]Yes [x]No

C-1) Required for all but Report Only VENs.
C-2) All VTNs and Simple HTTP VENs must support this requirement.



Implementation Capabilities and Configuration
For each of the questions below, indicate if the implementation has the necessary functionality, configurability, and documentation to successfully complete the certification testing process.

Item	ity, and documentation to successfully complete the certification to	Supp	
1	Does the implementation being submitted for certification support the capabilities outlined in the DUT Implementation Limits section of the OpenADR 2.0b Test Specification documentation? Note that these limits do not imply minimum market needs for a "b" profile implementation.	[x]Yes	[]No
2	Does the implementation being submitted for certification support methodologies necessary to trigger specific actions during test execution as outlined in the DUT Configuration Requirements section of the OpenADR 2.0b Test Specification documentation?	[x]Yes	[]No
3	Have you attached documentation to this PICS statement regarding how to configure the implementation as outlined in Appendix A of the OpenADR Certification Test Harness User Guide?	[x]Yes	[]No
4	Does the implementation being submitted for certification have pre-installed x.509 certificates from the OpenADR/NetworkFX portal?	[x]Yes	[ ]No
5	Does the VEN's being submitted for certification must have host authentication of the X.509 client certificate CN field disabled in order to avoid complex reconfiguration of the test harness and Openfire server? Answer No if not testing a VEN	[x]Yes	[ ]No
6	Does the VTN being submitted for certification have the XMPP Server per-configured for the user name of 11111111111 which the test harness uses to connect to the implementation's VTN XMPP server. Answer No if not testing a VTN or XMPP is not supported	[]Yes	[x]No
7)	Does the VTN being offer reports as part of its metadata report. If so, periodic reporting will be tested. Answer No if not testing a VTN or no reports are supported	[]Yes	[x]No



Optional Test Case Guidelines
Following test cases may be skipped if the criterion noted is met.

Item	est cases may be skipped if the criterion noted is met.  Criteria
1	Implementations will support either a push or pull exchange model. XMPP is always push, whereas HTTP may be either push or pull. Test cases are listed within Eclipse in a tree with branches labels Push or Pull. Only test cases appropriate to the exchange model should be run on the implementation.
2	If the implementation supports multiple transport and exchange model combinations, the full test suite shall be run across at least one push and one pull configuration. If there is more than one push configuration, then at least 4 non-negative randomly selected test cases shall be run across each service, with execution of the GO_9005_xx_xxx/GO_9010_xx_xxx security test being mandatory as part of the test cases run.
3	Test cases R?_?130_TH_VTN and R?_?140_TH_VTN may be skipped if HISTORY_USAGE reporting is not supported by a full function VEN. However, Report Only VENs must pass these test cases.
4	If the implementation is a Report Only VEN, then all of the tests under the EiEvent and EiOpt service headings may be skipped as these services are not supported.
5	If the answer to question 7 in the Implementation Capabilities and Configuration section is No and the implementation is a VTN, the following test cases may be skipped:  R1_3080_TH_VEN R1_8080_TH_VEN R1_3090_TH_VEN R1_3090_TH_VEN R1_3100_TH_VEN R1_3100_TH_VEN R1_3100_TH_VEN R1_8120_TH_VEN
6	If the VEN cannot send an Empty oadrDisributeEvent skip test case A_E0_0020
7	If the VTN cannot be configured to set oadrResponseRequired to never skip test cases A_E2_0468, A_E2_0480, A_E2_0498, A_E3_0468, A_E3_0480, and A_E3_0498
8	If VEN cannot be configure with multiple Market Context, skip test case A_E1_0285 and A_E0_0285
9	If the implementation cannot resend an unchanged payload, the test case A_E3_0680 can be skipped.



10	If the VTN cannot set a ramp up period skip test cases A_E2_0527 and
10	A_E3_0527
	A_L3_0327
11	If the VTN cannot configure multiple intervals in an event skip test case
11	SOURCE OF THE SECOND CONTRACTOR OF THE SECOND SECON
	A_E2_0432 and A_E3_0432
12	If a VTN cannot set an event's priority skin test case A F2 0510 A F2 0510
12	If a VTN cannot set an event's priority skip test case A_E2_0510, A_E3_0510,
	A_E2_ 0520, and A_E3_0520
13	If the VTN does not support configuration of eiTarget subelements, skip test
15	
	case A_E3_0435 and A_E2_0435.
14	If the VTN does not support configuration of randomization with a startafter
	element skip test cases A_E2_0685 and A_E3_0685.
15	If the VEN cannot be configured to request reports from VTN skip test case
	R1_3070_TH_VTN_1, R0_8070_TH_VTN_1, R1_3080_TH_VTN_1,
	RO_8080_TH_VTN_1, R1_3090_TH_VTN_1, R0_8090_TH_VTN_1,
	R1_3100_TH_VTN_1, R0_8100_TH_VTN_1, R1_3120_TH_VTN_1 and
	RO_8120_TH_VTN.
16	If the VTN or VEN cannot be configured to send piggy back report requests and
	report cancellation payloads skip test cases R1_3050_TH_VEN,
	RO_8050_TH_VEN_1, R1_3060_TH_VEN, RO_8060_TH_VEN,
	R1_3120_TH_VTN_1 and R0_8120_TH_VTN.

# **Pull VEN Configuration**

DUT : Gridwiz OpenADR 2.0b VEN Standard SDK

Characteristic	Test Harness (VTN) Property	DUT VEN Configuration
ven ID of the DUT	VEN_ID=DUT_VEN	DUT_VEN
vtnID of the test harness	VTN_ID=TH_VTN	TH_VTN
Market Context Associated with VEN	DR_MarketContext_1_Na me= http://MarketContext1 DR_MarketContext_2_Na me=	http://MarketContext1 http://MarketContext2
	http://MarketContext2 ResourceIDs=	
Resource Supported	resource1, resource2,resource3,r esource4	resource1, resource2, resource3, resource4 Thermostat,Strip_Heater
	Device_Class=Thermost at,Strip_Heater	
If the DUT requires a special string to invoke a test event, add it to properties	TestEventString=Test Event	
HTTP Configuration	Transport_Type=HTTP HTTP_VtnURL_Port=8080 HTTP_Security= HTTP_SHA1_Security	