

OpenADR 2.0b

Protocol Implementation Conformance Statement (PICS)

Version 1.0.6 Valid for Certification as of September 10, 2013

Manufacturer:	Korea Electronics Technology Lust	itute
Product Type:	VEH	
Product Name:	KETI OpenADR 2.06 VEN Softus	are
Firmware Revision:	VIO	
Tested OpenADR 2.0b Profile Spec version:	1.0.6	

Disclaimer:

The information provided in this document can be made available to the general public in order to identify the tested versions, features and options.

By signing this document, the manufacturer confirms that all information provided in this document is correct and the applicable features have been tested.

Manufacturer Name: <u>Rovea</u> <u>Electronics</u> <u>Technology</u>	Institute
Representative Name and Title:	
Signature:	
Date:	



Revisions:

Version Changes		Date/Editor
1.0.0	Released Version	06/28/13
1.0.1	 Added additional optional test case conditions 	07/28/13
1.0.2	 Added test case A_E1_0285 and A_E0_0285 to optional list 	08/15/13
1.0.4	 Added test case A_E3_0680 to optional list 	08/20/13
1.0.5	 Added the following test cases to optional list. A_E2_0435, A_E3_0435, A_E2_0685, A_E3_0685, R1_3070_TH_VTN_1, R0_8070_TH_VTN_1, R1_3080_TH_VTN_1, R0_8080_TH_VTN_1, R1_3090_TH_VTN_1,R0_8090_TH_VTN_1, R1_3100_TH_VTN_1, R0_8100_TH_VTN_1, R1_3120_TH_VTN_1, R0_8120_TH_VTN, R1_3050_TH_VEN, R0_8050_TH_VEN_1, R1_3060_TH_VEN, R0_8060_TH_VEN, R1_3120_TH_VTN_1 and R0_8120_TH_VTN. 	09/09/13
1.0.6	 Corrected typo. Removed test case A_E0_0295. Mentioned G0_9005. 	2/11/2014 EP, BD



Table of Contents

Revisions:	2
Introduction	4
References	4
Abbreviations and Conventions	4
Instructions for Completing the PICS	5
Documents required for final certification	5
Implementation and Supplier Information	6
Global Statement of Conformance	7
Roles	7
Profile Support	7
Transports /Exchange Pattern Support	7
Service Support	8
Security Support	8
Payload Schema Conformance	9
Operational Sequence Support	10
Standard Event Signal Support	11
Standard Report Support	11
Alliance "B" Profile Detailed Requirements	
Implementation Capabilities and Configuration	15
Optional Test Case Guidelines	16



Introduction

The purpose of this PICS document is to provide a mechanism whereby a supplier of an implementation based on the following requirements may provide information about the implementation in a standardized manner.

These requirements are drawn from the OASIS Energy Interoperation standard and related schemas. With the exception of OpenADR Alliance schema extensions, payloads generated by OpenADR 2.0b implementations should validate against the Energy Interop schemas.

Information provided by the supplier will be used to assess the implementation's compliance to the requirements, as well as to configure the certification tests performed on the implementation.

References

- OpenADR 2.0b Profile Specification 1.0
- OpenADR 2.0b Test Spec V1.0.6
- OpenADR 2.0b Schema

Abbreviations and Conventions

The PICS information comprises information in a tabular format as follows:

- Item Column A number which identifies the item in the table
- Capability Column A brief description of the requirement
- Reference Column or Section Header A reference to a specific requirement in the specification
- Status Column Contains notations regarding the requirements
 - o M Mandatory
 - o O Optional
 - o N/A Not applicable
 - o X Prohibited
 - O-i Qualified Optional (mutually exclusive or selectable options from a set identified with the same "I" value)
 - C-i –Conditional (status dependent on support of other optional requirements, identified in footnotes at bottom of table with "i" being a reference integer for the footnote(s))
- Support Column Yes or No answer is required. If feature is not applicable, answer No.
- Values Allowed Column Optional column representing set of values allowed.
- Values Supported Column Optional column where supplier can indicate a set of values supported by the implementation.

Note that all requirement references in the tables on the following pages are with respect to the OpenADR 2.0b Profile Specification, Version 1.0.



Instructions for Completing the PICS

The first part of the PICS document, System Identification, is to be completed as indicated with the information necessary to fully identify both the supplier and the implementation.

The main part of the PICS document is a fixed format questionnaire. Answers to questionnaire items are to be provided in the rightmost column by simply marking an answer to indicate a choice, typically Yes or No.

If an implementation fails to support a mandatory item, or supports a prohibited item, the supplier should provide supplementary information with the PICS document explaining the rationale for the exception.

Note: The burden of interoperability falls to the VTN implementation. Therefore any certified VTN must support the 2.0A profile and the 2.0B profile including the applicable schemas.

Documents required for final certification

- This PICS document
- Manufacturers Declaration of Conformity
- Completed Test Report from appointed test house
- Product marketing description for website (50 words)
- Product picture or logo if applicable
- Web link to product

If you would like to postpone posting your product on the OpenADR Alliance website for a period of time (maximum 3 months), please fill out the following section.

(Manufacturer) herewith requests that t posted on the OpenADR Alliance product web page untilsubmittal).	
Name:	
Signature:	



Implementation and Supplier Information

Date of Statement	17 APRIL 2015
Product Name	KETI OpenADR 2:06 VEN Software
Product Model Number	KETI-OADR-VEN
Version Number(s)	[,0
Non-Default Hardware Configuration	MA
Non-Default Software Configuration	N/A
Supplier Name, Address, Phone, Email	korea Te Electronics Technology Institute. *25, Saenari-ro, Bundany-gu, Seongnam-Si, Cayeonggi-do, 463-816, korea
Contact name, email, phone for questions	Jungmee Yun yungm@ keti.ve.kr +82-31-189-75/6



Global Statement of Conformance

Requirement	Support		
Are all mandatory capabilities supported for the indicated roles supported by this implementation?	MYes []No		

Roles

Item	Role	Status	Support
1	VEN - Full Function	0-1	[YYes []No
3	VEN - Energy Reporting Only	0-1	[]Yes MNo
3	VTN	0-1	[]Yes [Mo

⁰⁻¹⁾ Must answer Yes to one Role. Note that if an implementation supports both VEN and VTN functionality, two separate PICS documents should be submitted, one for each role.

Profile Support

Requirements Reference: Conformance rule 506

Item	Role	Profile	Status	Support
1	VEN/VTN	"A" Profile	C -1	[]Yes [MNo
2	VEN/VTN	"B" Profile	M	[]Yes []No

C-1) VTNs must support the A

Transports / Exchange Pattern Support

Requirements Reference: Figure 1. OpenADR 2.0 Certification Levels and conformance rule 37

Item	Role	Transport	Status	Support
1	VEN/VTN	SimpleHTTP - Pull	C-1	[MYes []No
2	VEN/VTN	SimpleHTTP - Push	C-1	[]Yes [YNo
3	VEN/VTN	XMPP - Push	C-1	[]Yes MNo

C-1) VTNs must support all transports and exchange patterns.

<

C-1) VENs may support ONLY the B profile

C-1) VENs must support at least one item from the list. If SimpleHTTP items are selected this must include the "SimpleHTTP-Pull" option from the list.



Service Support

Requirements Reference: Section 7.2.2 and conformance rules 501 and 507

Item	Role	Service	Status	Support
1	VEN/VTN	EiEvent	C-1	[/Yes []No
2	VEN/VTN	EiOpt	C-1	[/]Yes []No
3	VEN/VTN	EiReport	M	Yes []No
4	VEN/VTN	RiRegisterParty	M	MYes []No
5	VEN/VTN	OadrPoll	C-2	[]Yes []No

C-1) VTNs and Full Function VENs must support Services. Not supported by Report Only VENs.

Security Support

Requirements Reference: Conformance rules 67, 68, and 514

Item	Role	Security	Status	Sup	port
1	VEN	SHA1 Security -TLS 1.0, 1.1 -Client and server x.509 certs with SHA1 -Alliance RSA or ECC SHA1 Ciphers -SASL_EXTERNAL (XMPP Only)	C-1	[]Yes	[YNo
2	VTN	SHA1 Security -TLS 1.0, 1.1 -Client and server x.509 certs with SHA1 -Alliance RSA and ECC SHA1 Ciphers -SASL_EXTERNAL (XMPP Only)	C-1	[]Yes	lyno
3	VEN	SHA2 Security -TLS 1.2 -Client and server x.509 certs with SHA2 -Alliance RSA or ECC SHA2 Ciphers -SASL_EXTERNAL (XMPP Only)	C-2	(l)Yes	[]No
4	VTN	SHA2 Security -TLS 1.2 -Client and server x.509 certs with SHA2 -Alliance RSA and ECC SHA2 Ciphers -SASL_EXTERNAL (XMPP Only)	C-2	[]Yes	[JNo
5	VEN/VTN	XML Signatures	0	[]Yes	No

C-1) Support for these options is prohibited past an Alliance-defined grace period.

C-2) VTNs must support; VENs must support if simpleHTTP transport is supported.

C-2) Support for these options is mandatory past an Alliance-defined grace period. Select option appropriate to role, mark other as N/A.



Payload Schema Conformance

For each payload generated by a VEN or VTN, indicate if it conforms to the OpenADR B Profile schema. Note that the Status is relative to the Role listed.

Item	Role	Payload	Status for Role	Validates Against B Schema
1	VEN-Pull	oadrPoll	C-1	MYes []No
2	VEN	oadrRequestEvent	C-2	[YYes []No
3	VEN	oadrCreatedEvent	C-2	[Yes []No
4	VEN	oadrCreateOpt	C-2	[Yes []No
5	VEN	oadrCancelOpt	C-2	[YYes []No
6	VTN	oadrCanceledOpt	C-2	[Yes []No
7	VEN	oadrQueryRegistration	М	[YYes []No
8	VEN	oadrCreatePartyRegistration	M	[]Yes []No
9	VEN/VTN	oadrResponse	M	[MYes []No
10	VEN/VTN	oadrCancelPartyRegistration	M	Yes []No
11	VEN/VTN	oadrCanceledPartyRegistration	M	[Yes []No
12	VEN/VTN	oadrRegisterReport	М	MYes []No
13	VEN/VTN	oadrRegisteredReport	M	[^M Yes []No
14	VEN/VTN	oadrCreateReport	M	[MYes []No
15	VEN/VTN	oadrCreatedReport	М	MYes []No
16	VEN/VTN	oadrUpdateReport	M	MYes []No
17	VEN/VTN	oadrUpdatedReport	М	[/]Yes []No
18	VEN/VTN	oadrCancelReport	М	MYes []No
19	VEN/VTN	oadrCanceledReport	M	MYes []No
20	VTN	oadrCreatedOpt	C-2	[]Yes MNo
21	VTN	oadrDistributeEvent	C-2	[]Yes MNo
22	VTN	oadrCreatedPartyRegistration	M	[]Yes MNo
23	VTN	oadrRequestReregistration	М	[]Yes [MNo

C-1) VENs with SimpleHTTP push support must support oadrPoll, other implementations must not.

C-2) All implementations must support these options except for Report Only VENs.



Operational Sequence Support

The table below demonstrates the operational sequences and the conditional behavior for each of the services. The VEN oadrPoll interaction pattern and push HTTP acknowledgement (empty payload) of oadrDistributeEvent are not shown in the table. Indicate if all of the behavior shown in each section is supported by the implementation. Brackets are used to indicate conditional behavior which must be supported. Requirements reference: All figures in the B profile specification with interaction diagrams

Item	Service	App Level Exchange Sequence	Status	Sup	port
1	EiEvent	{VEN: RequestEvent {Reply Limit}} VTN: oadrDistributeEvent {Response Required, baseline} {VEN: oadrCreatedEvent {Opt State} VTN: oadrResponse }	C-1	[\]Yes	[]No
2	EiOpt	VEN: oadrCreateOpt {Availability schedule} VTN: oadrCreatedOpt VEN: oadrCancelOpt VTN: oadrCanceledOpt VEN: oadrCreateOpt - {Event Opt State} VTN: oadrCreatedOpt	C-1	Myes	[]No
3	EiRegisterParty	VEN: oadrQueryRegistration VTN: oadrCreatedPartyRegistration VEN: oadrCreatePartyRegistration VTN: oadrCreatedPartyRegistration VEN/VTN: oadrCancelPartyRegistration VTN/VEN: oadrCanceledPartyRegistration VTN: oadrRequestReregistration VEN: oadrResponse VEN: oadrCreatePartyRegistration VTN: oadrCreatePartyRegistration VTN: oadrCreatePartyRegistration VTN: oadrCreatedPartyRegistration	M	MYes	[]No
4	EiReport	VEN/VTN: oadrRegisterReport VTN/VEN: oadrRegisteredReport (Create Report *} VEN/VTN: oadrCreateReport (Once or Periodic) VTN/VEN: oadrCreatedReport VEN/VTN: oadrUpdateReport VTN/VEN: oadrUpdateReport {Cancel Report *} VEN/VTN: oadrUpdatedReport {Cancel Report *} VEN/VTN: oadrCancelReport VTN/VEN: oadrCancelReport {Report to Follow}	C-3	MYes	[]No
5	OadrPoll	VEN: oadrPoll VTN: Any payload sent by VTN	C-2	[V]Yes	[]No

C-1) All implementations must support these options, except for Report Only VENs.

C-2) Required for SimpleHTTP Pull VENs only.

C-3)VENs and VTNs are not required to demonstrate initiating piggyback report requests and report cancellations (*), but must understand them and act upon them if received from the other party. All other payload interactions shown are mandatory.



Standard Event Signal Support

Indicate which of the following Alliance-defined standard signals are supported by the VEN or VTN .

Requirements Reference: Conformance rule 510

Item	Role	Signal Name	SignalType	Status	Sup	Support	
1	VEN/VTN	SIMPLE		М	YJYes	[]No	
2	VEN/VTN	ELECTRICITY_PRICE	Price	М	MYes	[]No	
3	VEN/VTN	LOAD_DISPATCH	setpoint	М	[/]Yes	[]No	

¹⁾ The Alliance was still determining VTN report support at the time this was drafted.

Standard Report Support

Indicate which of the following Alliance-defined standard reports are offered as part of report registration by the VEN or VTN. Requirements Reference: Conformance rule 510

Item	Role	Report Name	Status	Support
1	VEN	METADATA	M	Yes []No
2	VEN	TELEMETRY_UASGE	М	[Yes []No
3	VEN	TELEMETRY_STATUS	M	[Yes []No
4	VEN	HISTORY_USAGE	C-1	[]Yes [MNo
5	VTN	METADATA	M	[]Ves MNo

C-1) Optional for full function VENs; mandatory for Report Only VENs.



Alliance "B" Profile Detailed Requirements

In addition to the requirements defined by the schema, the OpenADR 2.0b Profile has a detailed set of conformance rules that define the expected behavior of VTN and VEN implementations. As these rules already reflect the testable requirements, there is no need to relist them here. Please refer to the OpenADR 2.0b Profile Specification while indicating which of the following conformance rules are supported by the implementation.

Item (Rule)	Role	Status	Support
1	VTN	C-1	[]Yes [YNo
2	VTN	C-1	[]Yes [YNo
3	VTN	C-1	[]Yes [YNo
4	VTN	C-1	[]Yes MNo
5	VTN	C-1	[]Yes MNo
6	VEN	C-1	MYes []No
8	VTN	C-1	[]Yes MNo
9	VTN	C-1	[]Yes [YNo
10	VTN	C-1	[]Yes [YNo
12	VEN	C-1	MYes []No
13	VTN	C-1	[]Yes MNo
14	VTN	C-1	[]Yes MNo
15	VTN	C-1	[]Yes MNo
16	VTN	C-1	[]Yes MNo
17	VTN	C-1	[]Yes MNo
18	VEN/VTN	C-1	MYes []No
19	VEN	C-1	YYes []No
20	VTN	C-1	[]Yes MNo
21	VEN/VTN	C-1	Myes []No
22	VEN	C-1	MYes MNo
23	VEN/VTN	C-1	MYes []No
25	VTN	C-1	[]Yes [JNo
27	VTN	C-1	[]Yes MNo
29	VTN	C-1	[]Yes MNo
30	VEN	C-1	MYes []No
31	VEN	C-1	MYes []No
32	VEN/VTN	C-1	Vyes []No
33	VEN/VTN	C-1	[Yes []No
35	VEN	C-1	MYes []No
36	VEN	C-1	MYes []No
37	VEN	C-1	V/Yes []No
38	VTN	C-1	[]Yes Y]No
40	VTN	C-1	[]Yes MNo
41	VTN	C-1	[]Yes [/No
42	VEN/VTN	C-1	MYes []No
43	VEN	C-1	V]Yes []No
45	VEN/VTN	C-1	Y]Yes []No
46	VEN/VTN	C-1	V]Yes []No
47	VEN/VTN	C-1	V/Yes []No
48	VEN/VTN	C-1	V/Yes []No
50	VTN	C-1	[]Yes MNo
51	VEN/VTN	C-1	MYes []No
52	VTN	C-1	Y]Yes Y]No



Item Rule)	Role	Status	Support
53	VEN/VTN	C-1	[\Yes []No
56	VEN	C-1	MYes []No
57	VEN/VTN	C-1	MYes []No
58	VEN	C-1	MYes []No
59	VEN	C-1	MYes []No
60	VEN	C-1	MYes []No
61	VEN	C-1	Myes []No
62	VEN	C-1	MYes []No
63	VTN	C-1	[]Yes MNo
65	VEN	C-1	[MYes []No
66	VEN/VTN	C-1	Y]Yes []No
67	VEN/VTN	C-1	Myes []No
68	VEN/VTN	C-1	MYes []No
100	VTN	C-1	[]Yes []No
101	VTN	C-1	[]Yes MNo
102	VTN	C-1	[]Yes MNo
103	VTN	C-1	[]Yes MNo
104	VTN	C-1	[]Yes MNo
105	VTN	C-1	[]Yes [MNo
106	VTN	C-1	
107	VTN	C-1	[]Yes \/No
108			
109	VTN VEN	C-1	[]Yes V]No
		C-1	[]Yes []No
110	VTN	C-1	[]Yes V]No
111	VEN/VTN	C-1	Y]Yes []No
112	VEN	C-1	V/Yes []No
113	VTN	C-1	[]Yes MNo
114	VEN	C-1	MYes []No
115	VTN	C-1	[]Yes VINo
116	VEN/VTN	C-1	MYes []No
200	VEN/VTN	C-1	V/Yes []No
201	VEN/VTN	C-1	MYes []No
202	VEN	C-1	MYes []No
203	VTN	C-1	[]Yes \[/]No
204	VEN	C-1	MYes []No
205	VTN	C-1	[]Yes V]No
206	VEN/VTN	C-1	[]No
207	VEN/VTN	C-1	MYes []No
208	VEN/VTN	C-1	[JYes []No
209	VEN/VTN	C-1	Yes []No
210	VEN/VTN	C-1	[]No
211	VEN/VTN	C-1	√]Yes []No
300	VEN/VTN	M	[]Yes []No
301	VEN/VTN	M	V/Yes []No
302	VEN/VTN	M	[]No
303	VEN/VTN	M	V/Yes []No
304	VEN/VTN	M	Y]Yes []No
305	VEN/VTN	M	V]Yes []No
306	VEN/VTN	M	Y]Yes []No
307	VEN/VTN	M	V]Yes []No
308	VEN/VTN	M	[]Yes []No
309	VEN/VTN	M	(V)Yes []No



Item (Rule)	Role	Status	Support
311	VEN/VTN	М	Y]Yes []No
312	VEN/VTN	М	V/Yes []No
313	VEN/VTN	M	√[]Yes []No
314	VEN/VTN	M	Y]Yes []No
315	VEN/VTN	M	/]Yes []No
316	VEN/VTN	M	Yes []No
317	VEN/VTN	M	√]Yes []No
318	VEN/VTN	M	Yes []No
319	VEN/VTN	M	YYes []No
321	VEN/VTN	M	√]Yes []No
322	VEN/VTN	M	/]Yes []No
324	VEN/VTN	M	Yes []No
325	VEN/VTN	M	Yes []No
327	VEN/VTN	M	\(\frac{1}{2}\)Yes []No
328	VEN/VTN	M	√/]Yes []No
329	VEN/VTN	M	Y]Yes []No
330	VEN/VTN	M	Y]Yes []No
331	VEN/VTN	M	√{]Yes []No
333	VEN/VTN	M	V]Yes []No
334	VEN/VTN	M	Y]Yes []No
335	VEN/VTN	M	V[]Yes []No
336	VEN/VTN	M	V/]Yes []No
337	VEN/VTN	M	Y]Yes []No
338	VEN/VTN	M	
339	VEN/VTN	M	
340	VEN/VTN	M	
341	VEN/VTN	M	Y]Yes []No Y]Yes []No
342	VEN/VTN	M	Yes []No
343	VEN/VTN	M	Y]Yes []No
400	VEN/VTN	M	Y]Yes []No
401	VEN/VTN	M	7
402	VEN/VTN	M	7
403	VEN/VTN	M	
404	VEN/VTN	M	√[]Yes []No √[]Yes []No
405	VEN/VTN	M	
406	VEN/VTN	M	√]Yes []No √]Yes []No
407	VEN/VTN	M	Yes []No
500	VEN/VTN	C-2	√[]Yes []No
501	VEN/VTN	C-2	Y]Yes []No
502	VEN/VTN	C-2	Yes []No
506	VEN/VTN	M	Y]Yes []No
507	VEN/VTN	M	Y]Yes []No
508	VEN	M	\[/]Yes []No
509	VEN/VTN	M	\(\frac{4}{2}\)Yes []No
510	VEN/VTN	M	√]Yes []No
511	VEN/VTN	M	U/)Yes []No
512	VEN/VTN	M	[]Yes []No
514	VEN/VTN	0	[]Yes V/No
515	VEN/VTN	M	√]Yes []No

C-1) Required for all but Report Only VENs.
C-2) All VTNs and Simple HTTP VENs must support this requirement.



Implementation Capabilities and Configuration

For each of the questions below, indicate if the implementation has the necessary functionality, configurability, and documentation to successfully complete the certification testing process.

Item	Description	Sup	port
1	Does the implementation being submitted for certification support the capabilities outlined in the DUT Implementation Limits section of the OpenADR 2.0b Test Specification documentation? Note that these limits do not imply minimum market needs for a "b" profile implementation.	YYes	[]No
2	Does the implementation being submitted for certification support methodologies necessary to trigger specific actions during test execution as outlined in the DUT Configuration Requirements section of the OpenADR 2.0b Test Specification documentation?	∜]Yes	[]No
3	Have you attached documentation to this PICS statement regarding how to configure the implementation as outlined in Appendix A of the OpenADR Certification Test Harness User Guide?	MYes	[]No
4	Does the implementation being submitted for certification have pre-installed x.509 certificates from the OpenADR/NetworkFX portal?	¥]Yes	[]No
5	Does the VEN's being submitted for certification must have host authentication of the X.509 client certificate CN field disabled in order to avoid complex reconfiguration of the test harness and Openfire server? Answer No if not testing a VEN	\[]Yes	[]No
6	Does the VTN being submitted for certification have the XMPP Server per-configured for the user name of 111111111111 which the test harness uses to connect to the implementation's VTN XMPP server. Answer No if not testing a VTN or XMPP is not supported	[]Yes	UNO
7)	Does the VTN being offer reports as part of its metadata report. If so, periodic reporting will be tested. Answer No if not testing a VTN or no reports are supported	[]Yes	WNo



Optional Test Case Guidelines

Following test cases may be skipped if the criterion noted is met.

tem	Criteria	Supp	port
1	Implementations will support either a push or pull exchange model. XMPP is always push, whereas HTTP may be either push or pull. Test cases are listed within Eclipse in a tree with branches labels Push or Pull. Only test cases appropriate to the exchange model should be run on the implementation.	MYes	[]No
2	If the implementation supports multiple transport and exchange model combinations, the full test suite shall be run across at least one push and one pull configuration. If there is more than one push configuration, then at least 4 non-negative randomly selected test cases shall be run across each service, with execution of the GO_9005_xx_xxx/GO_9010_xx_xxx security test being mandatory as part of the test cases run.	MYes	[]No
3	Test cases R?_?130_TH_VTN and R?_?140_TH_VTN may be skipped if HISTORY_USAGE reporting is not supported by a full function VEN. However, Report Only VENs must pass these test cases.	MYes	[]No
4	If the implementation is a Report Only VEN, then all of the tests under the EiEvent and EiOpt service headings may be skipped as these services are not supported.	MYes	[]No
5	If the answer to question 7 in the Implementation Capabilities and Configuration section is No and the implementation is a VTN, the following test cases may be skipped: R1_3080_TH_VEN R1_8080_TH_VEN R1_3090_TH_VEN R1_8090_TH_VEN R1_8100_TH_VEN R1_3100_TH_VEN R1_8120_TH_VEN R1_8120_TH_VEN	[]Yes	Mno
6	If the VEN cannot send an Empty oadrDisributeEvent skip test case A_E0_0020	Ves	[]No
7	If the VTN cannot be configured to set oadrResponseRequired to never skip test cases A_E2_0468, A_E2_0480, A_E2_0498, A_E3_0468, A_E3_0480, and A_E3_0498	[]Yes	MNG
8	If VEN cannot be configure with multiple Market Context, skip test case A E1 0285 and A E0 0285	[]Yes	[]N



			1/
10	If the VTN cannot set a ramp up period skip test cases A_E2_0527 and A_E3_0527	[]Yes	[]No
11	If the VTN cannot configure multiple intervals in an event skip test case A_E2_0432 and A_E3_0432	[]Yes	NNO
12	If a VTN cannot set an event's priority skip test case A_E2_0510, A_E3_0510, A_E2_0520, and A_E3_0520	[]Yes	MNo
13	If the VTN does not support configuration of eiTarget subelements, skip test case A_E3_0435 and A_E2_0435.	[]Yes	MNo
14	If the VTN does not support configuration of randomization with a startafter element skip test cases A_E2_0685 and A_E3_0685.	[]Yes	MNo
15	If the VEN cannot be configured to request reports from VTN skip test case R1_3070_TH_VTN_1, R0_8070_TH_VTN_1, R1_3080_TH_VTN_1, R0_8080_TH_VTN_1, R1_3090_TH_VTN_1, R0_8090_TH_VTN_1, R1_3100_TH_VTN_1, R0_8100_TH_VTN_1, R1_3120_TH_VTN_1 and R0_8120_TH_VTN.	Y]Yes	[]No
16	If the VTN or VEN cannot be configured to send piggy back report requests and report cancellation payloads skip test cases R1_3050_TH_VEN, R0_8050_TH_VEN_1, R1_3060_TH_VEN, R0_8060_TH_VEN, R1_3120_TH_VTN_1 and R0_8120_TH_VTN.	[]Yes	UNO